



LUBRICANTS™

POWER TO PERFORM™

HYLUBE HDX MG

First Quality Engine Oil for Naturally Aspirated Diesel Engines

DESCRIPTION

HYLUBE HDX MG are First Quality engine oil developed for Naturally Aspirated Diesel Engines. The product is made from the paraffinic base stocks and fortified with selected additives to deliver satisfactory performance in busses, trucks, LCVs designed on Pre-Bharat Stage-I norms. The product is particularly suitable for the older diesel engines requiring lower detergency.

HYLUBE HDX MG oils have been multi-graded to 20W 40 & 20W 50 viscometrics to facilitate easy starting even at lower ambient temperatures. The superior additive chemistry not only ensures greater protection of the engine against wear and rust, its balanced detergency helps to keep the engine clean and trouble free for longer service intervals.

APPLICATIONS

HYLUBE HDX MG oils are recommended for older busses, trucks, lcvs, agricultural and farm equipment like pump-sets, tractors, power-tillers, harvesters & DG sets requiring good quality diesel engine oils.

HYLUBE HDX MG oils can also be used in petrol engines to render satisfactory performance.

FEATURES & BENEFITS

- Protects engine from wear and rust
- Easy starting even at lower ambient temperatures
- Higher levels of engine cleanliness
- Longer oil life and equipment life
- Offers better fuel efficiency

MEETS REQUIREMENTS OF

- API CF/SF

PHYSICO-CHEMICAL PROPERTIES (TYPICAL)

HYLUBE HDX MULTIGRADE	20W 40	20W 50
Kinematic Viscosity, cSt @ 100°C	13.5 - 16.0	17 - 19
Viscosity Index	128	129
TBN, mg KOH/g	4.65	5.39
Flash Point, (COC) °C	220	220
Pour Point, °C	-27	-27